

New Holland Boomer™ 1000 & T1000 Series Sub-compact Tractor Specifications



Boomer 1020 Boomer 1025 T1010 T1030

MODEL	Boomer 1020/T1010	Boomer 1025/T1030
ENGINE		
Gross engine hp (kW)	20 (14.9)	26 (19.4)
PTO hp (kW)	15.5 (11.6)	19.7 (14.7)
Rated speed, rpm	3000	3000
Cylinders	3	3
Displacement, cu. in. (L)	58.2 (.95)	69.0 (1.1)
Fuel capacity, gal. (L)	7.1 (26.9)	7.1 (26.9)
TRANSMISSIONS		
Hydrostatic transmission	2-speed	2-speed
Min/Max forward speed with R4 tires, mph (k/hr)	0-10.3 (16.6)	0-10.3 (16.6)
BRAKES		
LocationSingle LH side.....	
TypeWet disc.....	
POWER TAKE OFF (PTO)		
Rear	540	540
Mid	2200	2200
HYDRAULICS		
Pump type	Gear	Gear
System typeOpen center.....	
Pump capacity, gpm (lpm)*	5.6 (21.2)	5.6 (21.2)
Implement flow, gpm (lpm)	3.75 (14.20)	3.75 (14.21)
Steering priority flow, gpm (lpm)	1.85 (7.0)	1.85 (7.0)
3-point hitch lift capacity, 24 in. behind the lift balls, lb. (kg)	700 (318)	700 (318)
3-point hitch controlSelf centering valve.....	
*@ rated speed		
AXLE OPTIONS		
FWD	Standard	Standard
Sensitrac™ Auto FWD	NA	Optional
DIMENSIONS (with R4 tires)		
Overall length with 3-point hitch, in. (mm)	96.3 (2445)	96.3 (2445)
Overall width (minimum), in. (mm)	46.4 (1180)	46.4 (1180)
Wheelbase, in. (mm)	55.1 (1400)	55.1 (1400)
Height to top of ROPS, in. (mm)	72.4 (1840)	72.4 (1840)
Ground clearance	7.3 (185)	7.3 (185)
Shipping weight w/R4 tires, lbs. (kg)	1455 (660)	1455 (660)
TIRE OPTIONS		
Turf Tires		
Front18x8.5-8, 4 PR (R3) Turf.....	
Rear26x12-12, 4 PR (R3) Turf.....	
Industrial Tires		
Front18x8.5-8, 4 Pr (R4) Ind.....	
Rear26x12-12, 4PR (R4) Ind.....	

- STANDARD EQUIPMENT:**
- Toolbox
 - Cup holder
 - Foldable ROPS
 - 12 Volt accessory power outlet

OPTIONAL EQUIPMENT:

FRONT ATTACHMENTS

- Loader
- Quick-attach snow blower
- Quick-attach rotary broom
- Quick-attach front blade

MID-MOUNT ATTACHMENTS

- 60" mid-mount mower
- Grass catcher

REAR ATTACHMENTS

- Finishing mowers
- Rotary tiller
- Ballast box

Visit our Web site at www.newholland.com/na. Or, call toll-free 866-NEW-HLND (866-639-4563).

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

New Holland Boomer™ 1030 & T1110 Compact Tractor Specifications



Boomer 1030 T1110

MODEL	BOOMER 1030/T1110
ENGINE	
Gross engine hp (kW)	28 (20.9)
PTO hp (kW)	20.5 (15.3)
Rated speed, rpm	3100
Cylinders	3
Aspiration	Natural
Displacement, cu.in. (L)	69.0 (1.1)
Fuel capacity, gal. (L)	7.1 (26.9)
TRANSMISSIONS	
Hydrostatic transmission	2 speed
MinMax forward speed with R4 tires, mph (k/hr)	0-11.2 (18.1)
BRAKES	
Location	Single LH side
Type	Wet disc
POWER TAKE OFF (PTO)	
Rear	540
Mid	2200
HYDRAULICS	
Pump type	Gear
System type	Open center
Pump capacity, gpm (lpm) @ rated speed	6.5 (24.6)
Implement flow, gpm (lpm) @ rated speed	4.65 (17.6)
Power steering priority flow, gpm (lpm) @ rated speed	1.85 (7.0)
3-point hitch lift capacity, 24 in. behind the lift balls, lb. (kg)	1000 (454)
3-point hitch control	Position
DIMENSIONS (with R4 tires)	
Overall length with 3-point hitch, in. (mm)	98.5 (2501)
Overall width (minimum), in. (mm)	52.0 (13205)
Wheelbase, in. (mm)	57.5 (1460)
Height to top of ROPS, in. (mm)	76.0 (1931)
Ground clearance	7.8 (197)
Shipping weight w/R4 tires, lbs. (kg)	1402 (677)
TIRE OPTIONS	
Turf tires	
Front	20x10.00-10 4PR R3
Rear	29x12.5-15 4PR R3
Industrial tires	
Front	20x10.0-10 4PR R4
Rear	29x12.5-15 4PR R4

STANDARD EQUIPMENT:

- Toolbox
- Cup holder
- Foldable ROPS
- Auxiliary power outlet

OPTIONAL EQUIPMENT:

FRONT ATTACHMENTS

- Loader
- Quick-attach snow blower
- Quick-attach rotary broom
- Quick-attach front blade

MID-MOUNT ATTACHMENTS

- 60" mid-mount mower
- Grass catcher

REAR ATTACHMENTS

- Finishing mowers
- Rotary tiller
- Ballast box