

New Holland Boomer™ 2000 & T2200 Series Compact Tractor Specifications



Boomer 2030 Boomer 2035 T2210 T2220

MODEL	BOOMER 2030/T2210	BOOMER 2035/T2220
ENGINE		
Engine gross HP (kW) @ 2600	31 (23.1)	35 (26.1)
PTO HP (kW)		
@ 2600 RPM gear	26.5 (19.8)	NA
@ 2600 RPM hydro	24.9 (18.6)	28.9 (21.6)
Cylinders/displacement, cu. in. (L)	3 / 91.3 (1.5)	3 / 101.4 (1.6)
Aspiration	Natural	
Fuel tank capacity, US gal. (L)	7.3 (27.6)	

TRANSMISSIONS	BOOMER 2030/T2210	BOOMER 2035/T2220
Std. transmission:		
Forward/reverse	9x3 gear	3-range HST
Optional transmission:		
Forward/reverse	3-range HST	—

PTO	BOOMER 2030/T2210	BOOMER 2035/T2220
Type	Live	
Standard	Rear @ 540 rpm	
Optional	Mid @ 2000 rpm	

HYDRAULICS	BOOMER 2030/T2210	BOOMER 2035/T2220
Type	Open center	
Pump rated output, GPM (L/min)	12.3 (46.5)	
Steering pump flow, GPM (L/min)	5.1 (19.4)	
Implement pump flow, GPM (L/min)	7.2 (27.1)	

3 POINT HITCH	BOOMER 2030/T2210	BOOMER 2035/T2220
Hitch type	Category I	
Hitch lift cap., lb. (kg) @ 24" behind lift point	1635 (743)	

AXLE OPTION	BOOMER 2030/T2210	BOOMER 2035/T2220
FWD	Standard	
SuperSteer™ w/Sensitrack™ Auto FWD	Optional	

DIMENSIONS w/R4 TIRES	BOOMER 2030/T2210	BOOMER 2035/T2220
Wheelbase, in. (mm)	63 (1600)	
Front axle clearance, in. (mm)	13 (330)	
Approximate ship weight, lb. (kg) (HST)	2605 (1182)	2620 (1188)
Minimum overall width @ Rear axle, in. (mm)	61.6 (1565)	
Overall length lower links extended, in. (mm)	112.4 (2855)	

HEIGHT, in. (mm)	BOOMER 2030/T2210	BOOMER 2035/T2220
w/ROPS folded	66.6 (1692)	
w/ROPS	84.9 (2156)	

TIRE OPTIONS	BOOMER 2030/T2210	BOOMER 2035/T2220
Ag Tires		
Front	17 x 4 R1	
Rear	11.2 x 24 R1	
Turf Tires		
Front	24 x 8.5-14 R3	
Rear	13.6 x 16 R3	
Turf Tires (Supersteer™ only)		
Front	27 x 10.5-15 R3	
Rear	41 x 14-20 R3	
Industrial Tires		
Front	25 x 8.5-14 R4	
Rear	15 x 19.5 R4	
Galaxy® "Turf Special" Tires*		
Front	25/10.50LL x 15	
Rear	41/18LL	

*Front end loader installation not compatible with tractors equipped with Galaxy® "Turf Special" golf and turf tires.

Galaxy is a registered trademark of Galaxy Tire & Wheel Co.

New Holland Boomer™ 3000 & T2300 Series Compact Tractor Specifications



Boomer 3040 Boomer 3045 Boomer 3050 T2310 T2320 T2330

MODEL	BOOMER 3040/ T2310			BOOMER 3045/ T2320			BOOMER 3050/ T2330
	GEAR	HYDRO	CAB	GEAR	HYDRO	CAB	GEAR
ENGINE							
Gross engine hp (kW)40 (29.9).....		45 (33.6).....			50 (37.3)
PTO HP (kW)							
Gear transmission	35.0 (26.1)	NA	NA	39.6 (29.6)	NA	NA	43.0 (32.1)
Hydrostatic transmission	NA	33.2 (24.8)	33.2 (24.8)	NA	37.8 (28.2)	37.8 (28.2)	NA
Rated speed, rpm2600.....		2600.....			2800
Cylinders4-cylinder.....		4-cylinder.....			4-cylinder
Displacement, cu. in. (L)121.7(2.0).....		135.2 (2.2).....			135.2 (2.2)
Alternator	40 amp	40 amp	55 amp	40 amp	40 amp	55 amp	40 amp
Fuel capacity, gal. (L)13 (49.2).....		13 (49.2).....			13 (49.2)
TRANSMISSIONS							
12x12 SSS transmission	Standard	NA	NA	Standard	NA	NA	Standard
Min/Max forward speed with R4 tires, mph (k/hr)96-14.26 (1.55-22.96).....		96-14.26 (1.55-22.96).....			96-14.26 (1.55-22.96)
Hydrostatic transmission	NA	...2-range w/ DualPower™...		NA	...2-range w/ DualPower™...		NA
Min/Max forward speed with R4 tires, mph (k/hr)3.52-16.78 (5.66-27.01).....		3.52-16.78 (5.66-27.01).....			3.52-16.78 (5.66-27.01)
BrakesWet disc.....		Wet disc.....			Wet disc
POWER TAKE OFF (PTO)							
Mid PTO	NA	Optional	Optional	NA	Optional	Optional	NA
Rear PTO							
TypeIndependent.....		Independent.....			Independent
Clutch typeWet disc.....		Wet disc.....			Wet disc
HYDRAULICS							
Pump typeOpen center.....		Open center.....			Open center
Pump capacity, gpm (lpm) @ rated speed9.8 (37.1).....		9.8 (37.1).....			9.8 (37.1)
Power steering pump, gpm (lpm) @ rated speed5.1 (19.4).....		5.1 (19.4).....			5.1 (19.4)
3-point hitch lift capacity*2330 (1057).....		2330 (1057).....			2330 (1057)
*24 in. behind the lift balls, lb. (kg)							
AXLE OPTIONS							
2WD	optional	NA	NA	NA	NA	NA	NA
FWDStandard.....		Standard.....			Standard
SuperSteer™ FWD w/Sensitrac™ Auto FWD	NA	Optional	Optional	NA	Optional	Optional	NA
DIMENSIONS, in (mm)							
Wheelbase73.5 (1867).....		73.5 (1867).....			73.5 (1867)
Wheelbase w/SuperSteer	NA	81.0 (2057)	81.0 (2057)	NA	81.0 (2057)	81.0 (2057)	NA
Overall length w/3-point horizontal125.2 (3180).....		125.2 (3180).....			125.2 (3180)
Overall length w/SuperSteer	NA	129.5 (3289)	129.5 (3289)	NA	129.5 (3289)	129.5 (3289)	NA
Overall minimum width (ag tires)66.6 (1692).....		66.6 (1692).....			66.6 (1692)
Overall height with ROPS	95 (2413)	95 (2413)	NA	95 (2413)	95 (2413)	NA	95 (2413)
Overall height to top of cab (tractor w/R4 tires)	NA	NA	90.1 (2288)	NA	NA	90.1 (2288)	NA

New Holland Boomer™ 3000 & T2300 Series Compact Tractor Specifications



Boomer 3040 Boomer 3045 Boomer 3050 T2310 T2320 T2330

MODEL	BOOMER 3040/ T2310			BOOMER 3045/ T2320			BOOMER 3050/ T2330 GEAR
	GEAR	HYDRO	CAB	GEAR	HYDRO	CAB	
VEHICLE WEIGHT, lbs (kg)							
FWD, (tractor w/R4 tires)	3295 (1494)	3476 (1577)	4026 (1826)	3497 (1586)	3565 (1617)	4115 (1866)	3497 (1586)
Vehicle weight with loader, lbs. (kg)	4500 (2040)	4681 (2123)	5231 (2372)	4702 (2132)	4770 (2163)	5320 (2412)	4702 (2132)
Vehicle weight with loader and mower, lbs. (kg)	5275 (2391)	5456 (2474)	6006 (2723)	5477 (2483)	5545 (2514)	6095 (2763)	5477 (2483)

TIRE OPTIONS

2WD Boomer 3040

Ag Tires

Front	7.5 x 15 F2
Rear	14.9 x 24 R1

Turf Tires

Front	25 x 8.5-14 R3
Rear	44 x 18-20 R3

ALL 4WD MODELS

Ag Tires

Front	8 x 16 R1
Rear	14.9 x 24 R1

Turf Tires

Front	27 x 10.5-15 R3
Rear	44 x 18-20 R3

Industrial Tires

Front	10 x 16.5 R4
Rear	17.5L x 24 R4

Galaxy® "Turf Special" Tires*

Front	27/12LL x 15
Rear	22.5LL x 16.1

*Front end loader installation not compatible with tractors equipped with Galaxy® "Turf Special" golf and turf tires.

Galaxy is a registered trademark of Galaxy Tire & Wheel Co.

Visit our Web site at www.newholland.com/na Or, call toll-free: 1-888-290-7377

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.